

# TRACTOR DRIVE RADIAL TIRE RANGE




**ATG** | 6 CONTINENTS. OVER 120 COUNTRIES. THE GLOBAL LEADER IN OFF-HIGHWAY TIRES.

- R-1 and R-1W tread depths
- Special high speed series
- Wide range of 65, 70, 75, 85, 90 and 95 aspect ratio tires
- High traction ability, low inflation pressure and efficient self-cleaning
- Durable tread rubber compound and enhanced comfort characteristics



# TRACTOR DRIVE

## TRACTOR RADIAL PROGRAM

					
(pg 4)	(pg 4)	(pg 5)	(pg 6-8)	(pg 9)	
<b>372 AGRIFLEX + &amp; AGRIFLEX</b>	<b>378 AGRISTAR XL</b>	<b>365 AGRISTAR</b>	<b>370 AGRISTAR</b>	<b>385 AGRISTAR</b>	
VF 620/70R 26* VF 600/70R 28 VF 600/60R 38*  IF 420/85R 28 IF 600/70R 28 IF 600/70R 30 IF 650/75R 30* IF 710/60R 30* IF 800/65R 32 IF 800/70R 32* IF 650/65R 34* IF 520/85R 38 IF 710/85R 38* IF 800/70R 38 IF 900/60R 38 IF 580/85R 42 IF 710/70R 42 IF 710/75R 42*	620/75R 30* 710/55R 30* 710/60R 30* 900/60R 32* 900/75R 32* 600/70R 34 710/60R 34* 650/75R 38 900/55R 38* 900/60R 38 710/75R 42* 900/50R 42* 900/60R 42*	<b>HIGH SPEED</b> 420/65R 20* 420/65R 24* 440/65R 24 480/65R 24* 540/65R 24* 420/65R 28* 440/65R 28* 460/65R 28* 480/65R 28 540/65R 28 600/65R 28 540/65R 30 600/65R 30 540/65R 34 600/65R 34 710/60R 34* 540/65R 38* 600/65R 38 650/65R 38 710/70R 38 650/65R 42 710/70R 42	200/70R 16 240/70R 16 260/65R 16 260/70R 16 280/65R 16 280/70R 16 280/70R 18 260/70R 20 280/70R 20 300/70R 20 320/70R 20 340/65R 20 360/70R 20 380/70R 20 380/70R 24 420/70R 24 480/70R 24 28.1R 26 (750/70R 26) 19.5LR 28 600/70R 28 800/70R 38 580/70R 42	<b>HIGH SPEED</b> 19.5LR 28 480/70R 28 HS 19.5 LR 30 480/70R 30 HS	<b>HIGH SPEED</b> 280/85R 20 320/85R 20 420/80R 28 420/85R 30 420/90R 30 380/85R 34 420/85R 34 460/85R 34 380/80R 38* 420/85R 38 460/85R 38 520/85R 38 650/85R 38 520/85R 42 420/80R 46 480/80R 46 480/80R 50

# TRACTOR DRIVE



(pg 10)

**845**  
**(FarmPRO 70)**

280/70R 20  
300/70R 20  
320/70R 20  
320/70R 24  
360/70R 24  
380/70R 24  
420/70R 24  
480/70R 24  
320/70R 28  
360/70R 28  
380/70R 28  
420/70R 28  
480/70R 28  
420/70R 30  
480/70R 30  
520/70R 30  
480/70R 34  
520/70R 34  
480/70R 38  
520/70R 38  
580/70R 38  
710/70R 38  
710/70R 42



(pg 11-12)

**842 / 846**  
**(FarmPRO 85)**

280/85R 20  
320/85R 20  
250/85R 24  
280/85R 24  
320/85R 24  
340/85R 24  
380/85R 24  
420/85R 24  
280/85R 28  
320/85R 28  
340/85R 28  
380/85R 28  
420/85R 28  
380/85R 30  
420/85R 30  
460/85R 30  
320/85R 32  
380/85R 34  
420/85R 34  
460/85R 34  
320/85R 36  
340/85R 36  
340/85R 38  
380/85R 38  
420/85R 38  
460/85R 38  
520/85R 38  
320/80R 42  
480/80R 42  
520/85R 42  
480/80R 46  
520/85R 46



(pg 13-15)

**356**

**FRONT DRIVE  
SPECIAL**

14.9R 26  
16.9R 26  
18.4R 26  
11.2R 28  
15.5R 38  
18.4R 42  
14.9R 46  
18.4R 46  
16.9R 24  
14.9R 26  
16.9R 26  
18.4R 26  
16.9R 28  
14.9R 30  
16.9R 30



(pg 16)

**387**

14.9LR 20  
16.9LR 30



(pg 17-18)

**550**

250/80R 16 IND  
340/80R 18 IND  
365/70R 18 IND  
405/70R 18 IND  
340/80R 20 IND  
360/70R 20 IND  
360/80R 20 IND  
300/80R 24 IND  
340/80R 24 IND  
360/80R 24 IND  
400/80R 24 IND  
420/65R 24 IND  
440/80R 24 IND  
460/65R 24 IND  
480/65R 24 IND  
540/65R 24 IND  
400/80R 28 IND  
440/80R 28 IND  
480/65R 28 IND  
540/65R 28 IND  
440/80R 30 IND  
480/80R 30 IND  
540/65R 30 IND  
600/70R 30 IND  
440/80R 34 IND  
480/80R 34 IND  
480/80R 38 IND  
540/80R 38 IND

600/65R 38 IND  
650/65R 38 IND  
650/85R 38 IND  
620/80R 42 IND  
650/65R 42 IND  
710/70R 42 IND

\* Under development





## TRACTOR DRIVE

### TRACTOR RADIAL IF / VF SERIES 372 AGRIFLEX + & AGRIFLEX

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum RCI Sr	PR, Stars Load Index	Infl. press	Recommend load, kg (lbs)							
		SW	OD					Speed	Speed, km/h (mph)						
				Not high and sustained torque; Road transport						Cyclic					
				mm	mm	mm	mm		mm	mm	mm	mm	Press. bar	Load	
		in	in	in	in	Symbol	psi	10	15	20	25 up to 65 km/h 15 up to 40 mph	70	Press. bar	Load	
								6	9	12		44	psi	10	
VF600/70R28	DW21B DW20B	625 24.6	1560 61.4	681 26.8	4570 179.9	173D	2.8 41	6960 15330	6500 14320	6500 14320	6500 14320	5920 13040	3.6 52	9100 20040	
IF420/85R28	W15 W14	448 17.6	1437 56.6	636 25	4261 167.8	145D	1.6 23	3630 8000	3240 7140	2970 6540	2900 6390	2640 5810	2.4 35	4060 8940	
IF600/70R28	DW21B DW20B	625 24.6	1560 61.4	695 27.4	4597 181	164D	2.4 35	6250 13770	5580 12290	5130 11300	5000 11010	4550 10020	3.2 46	7000 15420	
IF600/70R30	DW20	615 24.2	1610 63.4	720 28.3	4770 187.8	159D 165D	1.6 23 2.4 35	5470 12050 6440 14190	4890 10770 5750 12670	4480 9870 5280 11630	4375 9640 5150 11340	3980 8770 4690 10330	2.4 35 3.2 46	6125 13490 7210 15880	
IF 800/70R38 CFO	DW27B DW25B	820 32.3	2085 82.1	926 36.5	6100 240.2	184A8	2.4 35	11250 24780	10050 22140	9230 20330	9000 19820	- -	3.2 46	12600 27750	



### 378 AGRISTAR XL TRACTOR DRIVE RADIAL R-1W

Size	Rim	Unloaded Dimension		Loaded Static Radius	Rolling Circum.	PR, Stars Load Index	Infl. Press.	Recommended Load, kg (lbs)										
		SW	OD					Speed Symbol	bar psi	Speed, km/h (mph)						Field operation		
				Not high and sustained torque; Road transport						Field operation								
				mm in	mm in	mm in	mm in			mm in	mm in	Static	10 6	25 16	30 19	40 25	50 31	65 40
600/70R34	DW20B DW18L, W18L	610 24	1705 67.1	770 30.3	5035 198.2	160D 163A8	2.4 35	10350 22800	6750 14870	5330 11740	4570 10070	4930 10860	4730 10420	4500 9910	4100 9030	6900 15200	5920 13040	5280 11630
900/60R38	DW27 DW28	856 33.7	2032 80	912 35.9	5975 235.2	178D 181A8	2.4 35	17250 38000	11250 24780	8890 19580	7610 16760	8210 18080	7880 17360	7500 16520	6830 15040	11490 25310	9850 21700	8780 19340
710/75R42	DW23B	730 28.7	2140 84.3	965 38	6312 248.5	175D 178A8	2.4 35	15870 34960	10350 22800	8180 18020	7000 15420	7560 16650	7250 15970	6900 15200	6280 13830	10580 23300	9070 19980	8090 17820

## 365 HIGH SPEED

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	PR, Stars Load Index	Infl. press	Recommend load, kg (lbs)										
		SW	OD					Speed, km/h (mph)										
		mm in	mm in	mm in	mm in	Speed Symbol	Bar psi	Field	1) Not high and sustained torque; 2) Road transport					Non cyclic operation				
									25 16	40 25	50 31	65 40	70 44	Bar psi	10 6	15 9		
440/65R 24	W14L	447	1192	547	3555	128D	1.6	2070	2130	1970	1890	1800	1640	2.0	3060	2790		
	W13	18	46.9	21.5	140	131A8	23	4560	4690	4340	4160	3960	3610	29	6740	6150		
480/65R 28	W15L	477	1335	607	3959	136D	1.6	2580	2650	2450	2350	2240	2040	2.0	3810	3470		
	W14L	19	52.6	23.9	155.9	139A8	23	5680	5840	5400	5180	4930	4490	29	8390	7640		
		142D	2.4	3050	3140	2900	2780	2650	2410	3.0	4510	4110						
540/65R 28	W16L	530	1420	639	4184	142D	1.6	3050	3140	2900	2780	2650	2410	2.0	4510	4110		
	W15L	21	55.9	25.2	164.7	145A8	23	6720	6920	6390	6120	5840	5310	29	9930	9050		
	W18L	21	55.9	25.2	164.7	152A8	2.4	3740	3850	3560	3410	3250	2960	3.0	5530	5040		
		149D	35	8240	8480	7840	7510	7160	6520	44	12180	11100						
600/65R 28	DW20	594	1484	668	4374	147D	1.6	3540	3640	3370	3230	3075	2800	2.0	5230	4770		
	W18L	23	58.4	26.3	172.2	150A8	23	7800	8020	7420	7110	6770	6170	29	11520	10510		
540/65R 30	W18L	560	1486	668	4374	143D	1.6	3130	3230	2980	2860	2725	2480	2.0	4630	4220		
	W16L	22	58.5	26.3	172.2	143B	23	6890	7110	6560	6300	6000	5460	29	10200	9300		
		150D	2.4	3850	3970	3670	3520	3350	3050	3.0	5700	5190						
600/65R30	DW20	610	1542	697	4554	153A8	35	8480	8740	8080	7750	7380	6720	44	12560	11430		
	W18L	24	60.7	27.4	179.3	149D	1.6	3740	3850	3560	3410	3250	2960	2.0	5530	5040		
540/65R 34	W16L	533	1570	718	4670	145D	1.6	3340	3440	3180	3050	2900	2640	2.0	4930	4500		
	W15L	21	61.8	28.3	183.9	148A8	23	7360	7580	7000	6720	6390	5810	29	10860	9910		
	W18L	21	61.8	28.3	183.9	152D	2.4	4080	4210	3890	3730	3550	3230	3.0	6040	5500		
		155A8	35	8990	9270	8570	8220	7820	7110	44	13300	12110						
600/65R 34	W18L	602	1648	740	4846	151D	1.6	3970	4090	3780	3620	3450	3140	2.0	5870	5350		
	W16 DW20A	24	64.9	29.1	190.8	155A8	23	8740	9010	8330	7970	7600	6920	29	12930	11780		
540/65R38	W16L	540	1667	770	4989	153D	2.4	4200	4330	4000	3830	3650	3320	3.0	6210	5660		
	W18L	21	65.6	30.3	196.4	153D	35	9250	9540	8810	8440	8040	7310	44	13680	12470		
600/65R 38	W18L	594	1748	796	5169	155A8	23	9250	9070	8440	8190	8040	7310	29	13680	12470		
						162A8	2.4	5030	5180	4790	4590	4375	3980	3.0	7440	6780		
	W16 DW20A	23	68.8	31.3	203.5	159D	35	11080	11410	10550	10110	9640	8770	44	16390	14930		
						157D	2.4	5030	5180	4790	4590	4375	3980	3.0	7440	6780		
	160A8	35	11080	11410	10550	10110	9640	8770	44	16390	14930							
650/65R 38	DW20B	658	1825	826	5485	163D	2.4	5610	5780	5340	5120	4875	4440	3.0	8290	7560		
						166A8	35	12360	12730	11760	11280	10740	9780	44	18260	16650		
	DW18L	26	71.9	32.5	215.9	166D	2.5	6100	6280	5800	5570	5300	4820	3.1	9010	8220		
						169A8	36	13440	13830	12780	12270	11670	10620	45	19850	18110		
710/70R 38	DW23A	728	1950	874.1	5729	166D	1.6	6100	5990	5570	5410	5300	4820	2.0	9010	8220		
						166A8	23	13440	13190	12270	11920	11670	10620	29	19850	18110		
	W18	29	76.8	34.4	225.6	171D	2.4	7070	7290	6730	6460	6150	5600	3.0	10460	9530		
650/65R 42	DW20A	657	1945	882	5758	174A8	35	15570	16060	14820	14230	13550	12330	44	23040	20990		
						158D	1.6	4890	4800	4460	4340	4250	3870	2.0	7230	6590		
	W18	26	76.6	34.7	226.7	160A8	23	10770	10570	9820	9560	9360	8520	29	15930	14520		
						170D	3.2	6900	7110	6570	6300	6000	5460	4.0	10200	9300		
173A8	46	15200	15660	14470	13880	13220	12030	58	22470	20480								
710/70R 42	DW23B	740	2055	936	6178	173D	2.4	7480	7700	7120	6830	6500	5920	3.0	11050	10080		
						176A8	35	16480	16960	15680	15040	14320	13040	44	24340	22200		
	29	80.9	36.9	243.2	177D	3.2	8400	8650	8000	7670	7300	6640	4.0	12410	11320			
180A8	46	18500	19050	17620	16890	16080	14630	58	27330	24930								



# TRACTOR DRIVE

## 370 WIDE DEEP TREAD RADIAL TIRE "SEVENTY" R-1W

Size	Rim	Unloaded dimension		Loaded Static	Rolling Circum	PR, Stars	Infl. press	Recommend load, kg (lbs)								
		SW	OD	Radius	mm	Load Index		Speed Symbol	Bar psi	Speed, km/h (mph)					Field operation	
							Not high and sustained torque; Road transport					Low Torque		High Tor		
		mm in	mm in	mm in	mm in	Speed Symbol	Bar psi	Static	10 6	25 16	30 19	40 25	50 31	10 6	20 12	10 6
200/70R 16	W6	197	686	315	2047	94A8	2.4	1540	1010	740	720	670	670	940	800	720
		7.8	27	12.4	80.6	94B	35	3390	2220	1630	1590	1480	1480	2070	1760	1590
240/70R 16	W8 W9	245	740	337.0	2196	104A8	2.4	2070	1350	1000	960	900	820	1260	1080	960
		9.6	29.1	13.3	86.4	101 B	35	4560	2970	2200	2110	1980	1810	2780	2380	2110
260/65R 16	W9 W8	258	741	342	2217	106A8	2.4	2190	1430	1050	1020	950	860	1330	1140	1020
		10.2	29.2	13.5	87.3	103 B	35	4820	3150	2310	2250	2090	1890	2930	2510	2250
260/70R 16	W9 W8	269	780	351	2299	109A8	2.4	2370	1550	1140	1100	1030	940	1440	1240	1100
		10.6	30.7	13.8	90.5	106 B	35	5220	3410	2510	2420	2270	2070	3170	2730	2420
280/65R 16	W9 W8	278	780	362	2343	110A8	2.4	2440	1590	1180	1130	1060	960	1480	1270	1130
		10.9	30.7	14.3	92.2	107 B	35	5370	3500	2600	2490	2330	2110	3260	2800	2490
280/70R 16	W9	278	804	368	2392	112A8	2.4	2580	1680	1240	1200	1120	1020	1570	1340	1200
		10.9	31.7	14.5	94.2	109 B	35	5680	3700	2730	2640	2470	2250	3460	2950	2640
280/70R 18	W9 W8 W10	278	860	390	2544	114A8	2.4	2710	1770	1310	1260	1180	1070	1650	1420	1260
		10.9	33.9	15.4	100.2	111B	35	5970	3900	2890	2780	2600	2360	3630	3130	2780
260/70R 20	W9 W8	258	878	402	2612	113A8	2.4	2650	1730	1280	1230	1150	1050	1610	1380	1230
		10.2	34.6	15.8	102.9	110B	35	5840	3810	2820	2710	2530	2310	3550	3040	2710
300/70R 20	W9 W10	293	956	435	2833	110A8	1.6	2440	1590	1180	1130	1060	960	1480	1270	1130
		11.5	37.6	17.1	111.5	107B	23	5370	3500	2600	2490	2330	2110	3260	2800	2490
						120A8	2.4	3220	2100	1550	1500	1400	1270	1960	1680	1500
320/70R 20	W10 W9 W11					117B	35	7090	4630	3410	3300	3080	2800	4320	3700	3300
		325	986	445	2908	113A8	1.6	2650	1730	1280	1230	1150	1050	1610	1380	1230
		12.8	38.8	17.5	114.5	110B	23	5840	3810	2820	2710	2530	2310	3550	3040	2710
						123A8	2.4	3570	2330	1720	1660	1550	1410	2170	1860	1660
						120B	35	7860	5130	3790	3660	3410	3110	4780	4100	3660



## 370 WIDE DEEP TREAD RADIAL TIRE "SEVENTY" R-1W

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	PR, Stars Load Index	Infl. press	Recommend load, kg (lbs)								
		SW	OD					Speed, km/h (mph)								
				Not high and sustained torque; Road transport						Field operation						
				Low Torque		High Tor										
mm in	mm in	mm in	mm in	Speed Symbol	Bar psi	Static	10 6	25 16	30 19	40 25	50 31	10 6	20 12	10 6		
340/65R 20	W11 W10 W12	345 13.6	955 37.6	431 17	2820 111	114A8	1.6	2710	1770	1310	1260	1180	1070	1650	1420	1260
						111B	23	5970	3900	2890	2780	2600	2360	3630	3130	2780
						124A8	2.4	3680	2400	1780	1710	1600	1460	2240	1920	1710
						121B	35	8110	5290	3920	3770	3520	3220	4930	4230	3770
360/70R 20	W11 W10 W12	360 14.2	1042 41.0	468 18.4	3066 120.7	129A8	2.4	4260	2780	2050	1980	1850	1850	2590	2220	1980
						129B	35	9380	6120	4520	4360	4080	4080	5700	4890	4360
380/70R 20	W12 W11 W13	380 15	1082 42.6	484 19.1	3176 125	122A8	1.6	3450	2250	1670	1610	1500	1500	2100	1800	1610
						122B	23	7600	4960	3680	3550	3300	3300	4630	3960	3550
480/70R 24	W15L W14L W16L	479 18.9	1322 52.1	590 23.2	3873 152.5	138A8	1.6	5430	3540	2620	2530	2360	2150	3300	2830	2530
						135B	23	11960	7800	5770	5570	5200	4740	7270	6230	5570
620/70R 26	DW20B W18L	625 24.6	1500 59.1	660 26.0	4440 174.8	153A8	1.6	8400	5480	4050	3910	3650	3650	5110	4380	3910
						153B	23	18500	12070	8920	8610	8040	8040	11260	9650	8610
28.1R 26 (750/70R 26)	DW24 DW25	750 29.5	1750 68.9	774.2 30.5	5177 203.8	158A8	1.6	9780	6380	4720	4550	4250	4250	5950	5100	4550
						158B	23	21540	14050	10400	10020	9360	9360	13110	11230	10020
						172A8	2.4	14490	9450	6990	6740	6300	6300	8820	7560	6740
						172B	35	31920	20810	15400	14850	13880	13880	19430	16650	14850
600/70R28	W18L DW20B	592 23.3	1562 61.5	709 27.9	4671 183.9	161A8	2.8	10640	6940	5130	4950	4625	4250	6480	5550	4950
						158 B	41	23440	15290	11300	10900	10190	9360	14270	12220	10900
19.5 LR 30	W15L W14L W16L	479 18.9	1474 58	666 26.2	4351 171.3	141A8	1.6	5920	3860	2860	2760	2575	2340	3610	3090	2760
						138 B	23	13040	8500	6300	6080	5670	5150	7950	6810	6080
						156A8	3.4	9200	6000	4440	4280	4000	3640	5600	4800	4280
						153 B	49	20260	13220	9780	9430	8810	8020	12330	10570	9430
600/70R 30	DW20B DW18L W18L	627 24.7	1594 62.8	708 27.9	4715 185.6	152A8	1.6	8170	5330	3940	3800	3550	3550	4970	4260	3800
						152 B	23	18000	11740	8680	8370	7820	7820	10950	9380	8370
800/70R 38	DW25B DW23B DW27B	806 31.7	2082 82	929 36.6	6101 240.2	173A8	1.6	14950	9750	7220	6960	6500	6500	9100	7800	6960
						173 B	23	32930	21480	15900	15330	14320	14320	20040	17180	15330
580/70R 42	W18L	601 23.7	1900 74.8	864 34	5632 221.7	158A8	1.6	9780	6380	4720	4550	4250	4250	5950	5100	4550
						158 B	23	21540	14050	10400	10020	9360	9360	13110	11230	10020



# TRACTOR DRIVE

## 370 WIDE DEEP TREAD RADIAL TIRE "SEVENTY" R-1W HIGH SPEED

Size	Rim	Unloaded dimension		Loaded Static	Rolling Circum	PR,Stars	Infl.	Recommend load, kg (lbs)									
		SW	OD	Radius	mm in	Load Index	press	Speed, km/h (mph)									
								Not high and sustained torque; Road transport						Field operation			
		mm in	mm in	mm in	mm in	Speed Symbol	Bar psi	10 6	20 12	40 25	50 31	65 40	70 44	10 6	20 12	10 6	
19.5LR28 (480/70R28)	W15L	479	1423	640	4189	151A8	2.5	4740	3890	3460	3320	3160	2900	4420	3790	3630	
	W14L	18.9	56	25.2	164.9	145E	36	10440	8570	7620	7310	6960	6390	9740	8350	8000	
	W16L																
19.5LR30 (480/70R30)	W15L	479	1474	662	4335	150A8	2.4	4580	3750	3340	3200	3050	2800	4270	3660	3510	
	144E					35	10090	8260	7360	7050	6720	6170	9410	8060	7730		
	W14L	18.9	58	26.1	170.7	155A8	3.2	5310	4350	3880	3720	3540	3250	4960	4250	4070	
	149E					46	11700	9580	8550	8190	7800	7160	10930	9360	8960		





## 385 AGRI-TRACTION (85 Series) R-1W

### High Speed Radial Tubeless Speed Symbols A-8 and D

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circumference	PR, Stars: Load Index	Infl. press	Recommend load, kg (lbs)									
		SW	OD					Speed, km/h (mph)									
				Not high and sustained torque;					Field operation								
				Road transport										Low Torque		High Tc	
				Static	10	20	30	40	50	65	10	20	10				
mm	mm	mm	mm	Speed Symbol	Bar psi	6	12	19	25	31	40	6	12	6			
280/85R 20	W10	286	994	448	2930	109D	1.6	2370	1550	1270	1180	1120	1120	1030	1570	1340	1200
	W9	11.26	39.134	17.6	115.4	112A8	23	5220	3410	2800	2600	2470	2470	2270	3460	2950	2640
320/85R 20	W11	325	1044	465	3140	116D	1.6	2880	1880	1540	1440	1360	1360	1250	1900	1630	1460
	W10 W9	12.8	41.1	18.3	123.6	119A8	23	6340	4140	3390	3170	3000	3000	2750	4190	3590	3220
420/85R 28	W15L	450	1435	649	4239	136D	1.6	5150	3360	2760	2580	1950	1950	2240	2730	2340	2090
	W14L	17.7	56.5	25.6	166.9	139A8	23	11340	7400	6080	5680	4300	4300	4930	6010	5150	4600
	W13																
420/85R 30	W15L	453	1475	669	4366	137D	1.6	5290	3450	2830	2650	2500	2500	2300	3500	3000	2680
	W14L	18.1	58.1	26.3	171.9	140A8	23	11650	7600	6230	5840	5510	5510	5070	7710	6610	5900
	W13																
380/85R 34	W12	390	1520	694	4516	134D	1.6	4880	3180	2610	2440	2300	2300	2120	3220	2760	2460
	W13	15.4	59.8	27.3	177.8	137A8	23	10750	7000	5750	5370	5070	5070	4670	7090	6080	5420
	W11																
420/85R 34	W15L	450	1580	713	4696	139D	1.6	5590	3650	2990	2790	2650	2650	2430	3710	3180	2840
	W14L	17.7	62.2	28.1	184.9	142A8	23	12310	8040	6590	6150	5840	5840	5350	8170	7000	6260
	W13					144D	2.1	6440	4200	3440	3220	3075	3075	2800	4310	3690	3290
	W13					147A8	30	14190	9250	7580	7090	6770	6770	6170	9490	8130	7250
460/85R 34	W16L	490	1653	752	4900	144D	1.6	6440	4200	3440	3220	3075	3075	2800	4310	3690	3290
	W15L	19.3	65.1	29.6	192.9	147A8	23	14190	9250	7580	7090	6770	6770	6170	9490	8130	7250
	W14L																
420/85R 38	W15L	446	1670	766	4976	141D	1.6	5920	3860	3170	2960	2800	2800	2575	3920	3360	3000
	W14L	17.6	65.748	30.2	195.9	144A	23	13040	8500	6980	6520	6170	6170	5670	8630	7400	6610
	W13																
460/85R 38	W16L	490	1755	802	5221	146D	1.6	6900	4500	3690	3450	3250	3250	3000	4550	3900	3480
	W15L	19.3	69.094	31.6	205.5	149A8	23	15200	9910	8130	7600	7160	7160	6610	10020	8590	7670
	W14L																
520/85R 38	DW16L	522	1854	842	5494	152D	1.6	8170	5330	4370	4080	3875	3875	3550	5430	4650	4150
	DW18L	20.6	73	33.1	216.3	155A8	23	18000	11740	9630	8990	8540	8540	7820	11960	10240	9140
						166D	3.2	12190	7950	6520	6100	5800	5800	5300	8120	6960	6210
						169A8	46	26850	17510	14360	13440	12780	12780	11670	17890	15330	13680
650/85R 38	DW23A	700	2052	934	6088	170D	2.4	13800	9000	7380	6900	6500	6500	6000	9100	7800	6960
	DW21A	27.6	80.8	36.8	239.7	173A8	35	30400	19820	16260	15200	14320	14320	13220	20040	17180	15330
	DW20A																
520/85R 42 (20.8R 42)	DW18L	520	1950	901	5837	154D	1.6	8630	5630	4610	4310	4125	4125	3750	5780	4950	4410
	DW16L	20.5	76.8	35.5	229.8	157A8	23	19010	12400	10150	9490	9090	9090	8260	12730	10900	9710
						165D	2.8	11850	7730	6330	5920	5600	5400	5150	7840	6720	5920
						168A8	41	26100	17030	13940	13040	12330	11890	11340	17270	14800	13040
420/80R 46	W13	420	1861	860	5572	151D	2.4	7940	4750	4240	3970	3780	3440	3450	5290	4540	4040
	W12	16.5	73.3	33.9	219.4	162A2	35	17490	10460	9340	8740	8330	7580	7600	11650	10000	8900
	W14					159D	3.2	10060	6560	5380	5030	4790	4360	4375	6710	5750	5130
						170A2	46	22160	14450	11850	11080	10550	9600	9640	14780	12670	11300
480/80R 50	W15L	480	2060	958	6227	159D	2.4	10060	6560	5380	5030	4750	4750	4375	6650	5700	5080
	W14L	18.9	81.1	37.7	245.2	172A2	35	22160	14450	11850	11080	10460	10460	9640	14650	12560	11190
	W16L					165D	3.2	11850	7730	6330	5920	5600	5600	5150	7840	6720	5990
						176A2	46	26100	17030	13940	13040	12330	12330	11340	17270	14800	13190



# TRACTOR DRIVE

## 845 FARMPRO RADIAL 70 SERIES

Size	Rim	Unloaded Dimension		Loaded Static Radius	Rolling Circum.	Load Index	Infl. Press.	Recommended Load, kg (lbs)	
		SW	OD					Speed, km/h (mph)	
		mm in	mm in					40 25	50 31
280/70R20	W10	278	912	415	2706	116A8	2.4	1250	1140
	W9	10.9	35.9	16.3	106.5	113B	35	2750	2510
300/70R20	W9	293	956	435	2833	120A8	2.4	1400	1270
	W10	11.5	37.6	17.1	111.5	117B	35	3080	2800
320/70R20	W10	325	986	445	2908	123A8	2.4	1550	1410
	W9	12.8	38.8	17.5	114.5	120B	35	3410	3110
	W11								
320/70R 24	W10	319	1094	499	3260	116A8	1.6	1250	1250
		12.6	43.1	19.6	128.3	116B	23	2750	2750
360/70R 24	W11	357	1152	522	3420	122A8	1.6	1500	1500
	W10	14.1	45.4	20.6	134.6	122B	23	3300	3300
380/70R 24	W12	380	1190	538	3513	125A8	1.6	1650	1650
	15	46.9	21.2	138.3	125B	23	3635	3635	
420/70R 24	W13	418	1248	561	3672	130A8	1.6	1900	1900
	W12	16.5	49.1	22.1	144.6	130B	23	4190	4190
480/70R24	W15L	479	1316	588	3859	138A8	1.6	2360	2360
	18.9	51.8	23.1	151.9	138B	23	5200	5200	
320/70R 28	W10	319	1189	547	3551	119A8	1.6	1360	1360
		12.6	46.8	21.5	139.8	119B	23	3000	3000
360/70R 28	W11	357	1251	572	3722	125A8	1.6	1650	1650
		14.1	49.3	22.5	146.5	125B	23	3630	3630
380/70R 28	W12	380	1293	589	3837	127A8	1.6	1750	1750
	15	50.9	23.2	151.1	127B	23	3850	3850	
420/70R 28	W13	418	1349	611	3991	133A8	1.6	2060	2060
		16.5	53.1	24.1	157.1	133B	23	4540	4540
480/70R 28	W15L	479	1421	640	4188	140A8	1.6	2500	2500
	18.9	55.9	25.2	164.9	140B	23	5510	5510	
420/70R 30	W13	418	1398	636	4146	134A8	1.6	2120	2120
		16.5	55	25	163.2	134B	23	4675	4675
480/70R 30	W15L	479	1478	668	4365	141A8	1.6	2575	2575
	18.9	58.2	26.3	171.9	141B	23	5670	5670	
520/70R 30	W16L	516	1536	691	4525	145A8	1.6	2900	2900
	20.3	60.5	27.2	178.1	145B	23	6395	6395	
480/70R 34	W15L	479	1580	719	4686	143A8	1.6	2725	2725
	18.9	62.2	28.3	184.5	143B	23	6000	6000	
520/70R 34	W16L	516	1640	743	4851	148A8	1.6	3150	3150
	20.3	64.6	29.3	191	148B	23	6940	6940	
480/70R 38	W15L	479	1681	770	5005	145A8	1.6	2900	2900
	18.9	66.2	30.3	197	145B	23	6390	6390	
520/70R 38	W16L	516	1749	797	5191	150A8	1.6	3350	3350
	20.3	68.9	31.4	204.4	150B	23	7380	7380	
580/70R38	W18L	577	1827	828	5406	155A8	1.6	3875	3875
	22.7	71.9	32.6	212.8	155B	23	8540	8540	
710/70R 38	DW23B	716	1958	880	5768	172A8	2.4	6300	6300
		28.2	77.1	34.6	227.1	172B	35	13560	13560
710/70R 42	DW23B	716	2061	938	6080	173A8	2.4	6500	6500
		28.2	81.1	36.9	239.4	173B	35	14330	14330

## 842 / 846 FARMPRO RADIAL 85 SERIES

Size	Rim	Unloaded Dimension		Loaded Static Radius mm in	Rolling Circum. mm in	Load Index Speed Symbol	Infl. Press. bar psi	Recommended Load, kg (lbs)	
		SW	OD					Speed, km/h (mph)	
		mm in	mm in					40 25	50 31
280/85R 20	W10	288	984	447	2913	112A8	1.6	1120	1120
		11.3	38.7	17.6	114.7	112B	23	2470	2470
320/85R 20	W11	319	1052	472	3093	119A8	1.6	1360	1360
		12.6	41.4	18.6	121.8	119B	23	3000	3000
250/85R 24	W8	246	1036	476	3067	109A8	1.6	1030	1030
		9.7	40.8	18.7	120.7	109B	23	2270	2270
280/85R 24	W10	270	1090	495	3215	115A8	1.6	1215	1215
		11	43	19	126.5	115B	23.2	2673	2673
320/85R 24	W11	336	1148	515	3398	122 A8	1.6	1500	1500
		13.2	45.2	20.3	133.8	122 B	23	3307	3307
340/85R 24	W12	356	1181	530	3496	125A8	1.6	1650	1650
		14	46	21	137.6	125B	23.2	3630	3630
380/85R 24	W12	386	1252	557	3706	131A8	1.6	1950	1950
		15	49	22	145.9	131B	23.2	4290	4290
420/85R 24	W15L	418	1324	591	3879	137A8	1.6	2300	2300
		16.5	52.1	23.3	152.7	137B	23	5070	5070
280/85R28	W9 W10	280	1187	539	3514	118A8	1.6	1320	1320
		11	46.7	21.2	138.3	118B	23	2910	2910
320/85R 28	W11	325	1246	565	3688	124A8	1.6	1600	1600
		13	49	22	145.2	124B	23.2	3520	3520
340/85R 28	W12	360	1295	580	3833	127A8	1.6	1750	1750
		14	51	23	150.9	127B	23.2	3850	3850
380/85R 28	W12	380	1357	604	4002	133A8	1.6	2060	2060
		15	53	24	157.6	133B	23.2	4532	4532
420/85R 28	W15L	418	1425	630	4189	139A8	1.6	2430	2430
		16	56	25	164.9	139B	23.2	5346	5346
380/85R 30	W12	380	1408	630	4136	135A8	1.6	2180	2180
		15	55.4	24.8	162.8	135B	23	4800	4800
420/85R 30	W15L	431	1468	658	4331	140A8	1.6	2500	2500
		17	58	26	170.5	140B	23.2	5500	5500
460/85R 30	W16L	475	1534	684	4529	145A8	1.6	2900	2900
		19	60	27	178.3	145B	23.2	6380	6380
320/85R 32	W11	325	1357	625	4017	126A8	1.6	1700	1700
		12.8	53.4	24.6	158.1	126B	23	3750	3750
380/85R 34	W12	380	1510	680	4455	137A8	1.6	2300	2300
		15	59.4	26.8	175.3	137B	23	5070	5070
420/85R 34	W15L	420	1585	715	4646	142A8	1.6	2650	2650
		17	62	28	182.9	142B	23.2	5830	5830
460/85R 34	W16L	479	1637	733	4846	147A8	1.6	3075	3075
		19	64	29	190.7	147B	23.2	6765	6765
320/85R 36	W11	325	1458	675	4316	128A8	1.6	1800	1800
		12.8	57.4	26.6	169.9	128B	23	3970	3970
340/85R 36	W12	345	1492	689	4425	132A8	1.6	2000	2000
		13.6	58.7	27.1	174.2	132B	23	4410	4410
340/85R 38	W12	345	1543	714	4567	133A8	1.6	2060	2060
		13.6	60.7	28.1	179.8	133B	23	4540	4540
380/80R 38	W12	375	1578	728	4721	142A8	2.4	2650	2650
		14.8	62.1	28.7	185.9	142B	35	5840	5840
420/85R 38	W15L	415	1680	655	4973	144A8	1.6	2800	2800
		16	66	26	195.7	144B	23.2	6160	6160



# TRACTOR DRIVE

## 842 / 846 farmPRO RADIAL 85 SERIES

Size	Rim	Unloaded Dimension		Loaded Static Radius	Rolling Circum.	Load Index Speed Symbol	Infl. Press.	Recommended Load, kg (lbs)	
		SW	OD					Speed, km/h (mph)	
		mm in	mm in	mm in			40 25	50 31	
460/85R38	W16L	455	1740	783	5150 202.8	149A8	1.6 23	3250	3250
		17.9	68.5	30.8		149B		7165	7165
520/85R38	W16L	525	1850	830	5476 215.6	169A8	3.6 52	5800	5800
		20.7	72.8	72.7		169B		12790	12790
480/80R 42	DW16L	479	1835	841	5413 213.1	151A8	1.6 23.2	3450	3450
		19	72	33		151B		7590	7590
520/85R 42	DW16L	516	1951	888	5755 226.6	157A8	1.6 23.2	4125	4125
		20	77	35		157B		9075	9075
480/80R 46	DW16L	479	1936	880	5782 227.6	158A8	1.6 23	4250	4250
		18.9	76.2	34.6		158B		9350	9350
520/85R 46	DW16L	516	2049	937	6053 238.3	158A8	1.6 23	4250	4250
		20.3	80.7	36.9		158B		9360	9360





## 356 POWER DRIVE RADIAL R-1

Size	Rim	Unloaded Dimension		Loaded Static Radius	Rolling Circum.	PR, Stars Load Index	Infl. Press.	Recommended Load, kg (lbs)										
		SW	OD					Speed, km/h (mph)										
								Not high and sustained torque; Road transport							Field Operation			
		mm in	mm in	mm in	mm in	Speed Symbol	bar psi	Static	10 6	25 16	30 19	40 25	50 31	65 40	10 6	20 12	10 6	
14.9R 26	W13	378	1300	592	3857	** 127A8 124B	1.6 23	4030 8880	2630 5790	1940 4270	1870 4120	1750 3850	1590 3500	—	2450 5400	2100 4630	1870 4120	
	W12	14.9	51.2	23.3	151.9	133A8 129B	2.1 30	4740 10440	3090 6810	2290 5040	2200 4850	2060 4540	1870 4120	—	2880 6340	2470 5440	2200 4850	
16.9R 26	W15L	429	1370	624	4066	** 135A8 132B	1.6 23	5010 11040	3270 7200	2420 5330	2330 5130	2180 4800	1980 4360	—	3050 6720	2620 5770	2330 5130	
	W14L	16.9	53.9	24.6	160.1	138A8 135B	1.8 26	5430 11960	3540 7800	2620 5770	2530 5570	2360 5200	2150 4740	—	3300 7270	2830 6230	2530 5570	
18.4R 26	W16L	476	1426	643	4205	** 140A8 137B	1.6 23	5750 12670	3750 8260	2780 6120	2680 5900	2500 5510	2280 5020	—	3500 7710	3000 6610	2610 5900	
	W15L	18.7	56.1	25.3	165.6													
11.2R 28	W10	284	1220	556	3599	** 116A8 113B	1.6 23	2880 6340	1880 4140	1390 3060	1340 2950	1250 2750	1140 2510	—	1750 3850	1500 3300	1340 2950	
	W9	11.2	47.2	21.9	141.7													





# TRACTOR DRIVE

## 356 POWER DRIVE RADIAL R-1

Size	Rim	Unloaded Dimension		Loaded Static Radius	Rolling Circ. RCI	PR, Stars Load Index	Infl. Press.	Recommend Load, kg (lbs)									
		SW	OD					Speed, km/h (mph)									
								Constant Load								Cyclic Applications	
		mm in	mm in					mm in	mm in	Speed Symbol	bar psi	Static	10 6	25 16	30 19	40 25	50 31
18.4R 30	W16L	467 142A8	1545 23	712 13440	4618 8770	**	1.6	6100	3980	2940	2840	2650	2410	3710	3180	2840	
						6480	6260	5840	5310	8170	7000	6260					
						139B	2.8	8910	5810	4300	4150	3875	3530	5430	4650	4150	
						155A8	41	19630	12800	9470	9140	8540	7780	11960	10240	9140	
18.4R 34	W16L W15L	486 19.1	1671 65.8	750 29.5	4914 193.5	**	1.6	6440	4200	3110	3000	2800	2550	3920	3360	3000	
						144A8	23	14190	9250	6850	6610	6170	5620	8630	7400	6610	
						141B	2.8	9490	6190	4580	4410	4125	3750	5780	4950	4410	
						154B	41	20900	13630	10090	9710	9090	8260	12730	10900	9710	
13.6R38	W12 W11	345 13.6	1550 61	722 28.4	4664 183.6	**	1.6	4140	2700	2000	1930	1800	1640	2520	2160	1930	
						128A8	23	9120	5950	4410	4250	3960	3610	5550	4760	4250	
						125B	4.8	7940	5180	3830	3690	3450	3140	4830	4140	3690	
						151A8	70	17490	11410	8440	8130	7600	6920	10640	9120	8130	
18.4R 38	W16L W15L	480 18.9	1750 68.9	781 30.7	5217 205.4	**	1.6	6900	4500	3330	3210	3000	2730	4200	3600	3210	
						146A8	23	15200	9910	7330	7070	6610	6010	9250	7930	7070	
						143B	2.1	8170	5330	3940	3800	3550	3230	4970	4260	3800	
						152A8	30	18000	11740	8680	8370	7820	7110	10950	9380	8370	
						149B	2.8	12540	8180	6050	5830	5450	4960	7630	6540	5830	
						164B	41	27620	18020	13330	12840	12000	10930	16810	14410	12840	
						170A8	3.2	13800	9000	6660	6420	6000	5460	8400	7200	6420	
						167B	46	30400	19820	14670	14140	13220	12030	18500	15860	14140	
14.9R 46 (Des.350)	W13 W12	378 14.9	1824 71.8	841 33.1	5454 214.7	***	2.1	6100	3980	2940	2840	2650	2410	3710	3180	2840	
						142A8	30	13440	8770	6480	6260	5840	5310	8170	7000	6260	
						139B	2.5	6900	4500	3330	3210	3000	2730	4200	3600	3210	
						146A8	36	15200	9910	7330	7070	6610	6010	9250	7930	7070	
18.4R 46	W16L W15L	467 18.4	1958 77.1	903 35.6	5856 230.6	***	2.1	8910	5810	4300	4150	3875	3530	5430	4650	4150	
						155A8	30	19630	12800	9470	9140	8540	7780	11960	10240	9140	
						152B	3.5	16330	10650	7880	7600	7100	7100	9940	8520	7600	
						176A8	51	35970	23460	17360	16740	15640	15640	21890	18770	16740	



## 356 POWER DRIVE RADIAL R-1

Size	Rim	Unloaded Dimension		Loaded Static Radius	Rolling Circum.	PR, Stars Load Index	Infl. Press.	Recommended Load, kg (lbs)										
		SW	OD					Speed, km/h (mph)										
								Not high and sustained torque; Road transport										Field Operation
		mm in	mm in					mm in	mm in	Speed Symbol	bar psi	Static	10 6	25 16	30 19	40 25	50 31	65 40
15.5R 38	W14L	394	1570	724	4695	**	1.6	4880	3180	2350	2270	2120	1930	—	2970	2540	2270	
		15.5	61.8	28.5	184.8	134A8 131B		23	10750	7000	5180	5000	4670	4250	—	6540	5590	5000
18.4R 42	W16L W15L	467	1850	853	5532	**	1.6	7250	4730	3500	3370	3150	2870	—	4410	3780	3370	
						148A8 145B		23	15970	10420	7710	7420	6940	6320	—	9710	8330	7420
						***		2.1	8400	5480	4050	3910	3650	3320	—	5110	4380	3910
153A8 150B	30	18500	12070	8920	8610	8040	7310		—	11260	9650	8610						
14.9R 46 (Des.350)	W13 W12	378	1824	841	5454	****	2.5	6900	4500	3330	3210	3000	2730	—	4200	3600	3210	
						146A8 143B		36	15200	9910	7330	7070	6610	6010	—	9250	7930	7070
						149D		2.9	7480	4880	3850	3740	3560	3410	3250	4980	2470	3810
32	16480	10750	8480	8240	7840	7510	7160		10970	9410	8390							
18.4R 46	W16L W15L	467	1958	903	5856	***	2.1	8910	5810	4300	4150	3875	3530	—	5430	4650	4150	
						155A8 152B		30	19630	12800	9470	9140	8540	7780	—	11960	10240	9140

## 356 FRONT DRIVE SPECIAL R-1

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum.	PR, Stars Load Index	Infl. press	Recommend load, kg (lbs)									
		SW	OD					Speed, km/h (mph)									
								Not high and sustained torque; Road transport									
		mm in	mm in					mm in	mm in	Speed Symbol	Bar psi	Static	10 6	25 16	30 19	40 25	50 31
16.9R 24 Front	W15 W14L	429	1320	601	3916	**	1.6	4880	3180	2350	2270	2120	1930	2970	2540	2270	
		16.9	52	23.7	154.2	134A8 131B		23	10750	7000	5180	5000	4670	4250	6540	5590	5000
14.9R 26 Front	W13 W12	378	1300	592	3857	**	1.6	4030	2630	1940	1870	1750	1590	2450	2100	1870	
						127A8 124B		23	8880	5790	4270	4120	3850	3500	5400	4630	4120
16.9R 26 Front	W15L W14L	429	1370	624	4066	**	1.6	5010	3270	2420	2330	2180	1980	3050	2620	2330	
						135A8 132B		23	11040	7200	5330	5130	4800	4360	6720	5770	5130
18.4R 26 Front	W16L W15L	476	1426	643	4205	**	1.6	5750	3750	2780	2680	2500	2280	3500	3000	2680	
						140A8 137B		23	12670	8260	6120	5900	5510	5020	7710	6610	5900



# TRACTOR DRIVE

## 356 FRONT DRIVE SPECIAL R-1

Size	Rim	Unloaded dimension		Loaded Static Radius	Rolling Circum	PR, Stars Load Index	Infl. press	Recommend load, kg (lbs)								
		SW	OD					Speed, km/h (mph)								
								Not high and sustained torque; Road transport						Field operation		
								Static	10	25	30	40	50	Low Torque	High Tor	
mm in	mm in	mm in	mm in	Speed Symbol	Bar psi	Static	10 6	25 16	30 19	40 25	50 31	10 6	20 12	10 6		
16.9R 28 Front	W15L	429	1420	645	4206	**										
						136A8	1.6	5150	3360	2490	2400	2240	2040	3140	2690	2400
	W14L	16.9	55.9	25.4	165.6	133B	23	11340	7400	5480	5290	4930	4490	6920	5930	5290
						139A8	1.9	5590	3650	2700	2600	2430	2210	3400	2920	2600
						136B	28	12310	8040	5950	5730	5350	4870	7490	6430	5730
14.9R 30 Front	W13	378	1400	644	4180	**										
						129A8	1.6	4260	2780	2050	1980	1850	1680	2590	2220	1980
	W12	14.9	55.1	25.4	164.6	126B	23	9380	6120	4520	4360	4070	3700	5700	4890	4360
						***										
						134A8	2.1	4880	3180	2350	2270	2120	1930	2970	2540	2270
						131B	30	10750	7000	5180	5000	4670	4250	6540	5590	5000
16.9R 30 Front	W15L	429	1475	672	4378	***										
						141A8	2.1	5920	3860	2860	2760	2575	2340	3610	3090	2760
	W14L	16.9	58.1	26.5	172.4	138B	30	13040	8500	6300	6080	5670	5150	7950	6810	6080

## 387 TRACTOR DRIVE R-1

Size	Rim	Unloaded Dimension		Loaded Static Radius	Rolling Circum.	PR, Stars Load Index	Infl. Press.	Recommended Load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
								Not high and sustained torque; Road transport					Field operation
								Static	10	25	30	40	50
mm in	mm in	mm in	mm in	Speed Symbol	bar psi	Static	10 6	25 16	30 19	40 25	50 31		
14.9LR 20	W13	378	1075	481	3156	1198	1.6	3130	2040	1510	1460	1360	1250
						A	23	6890	4490	3330	3220	3000	2750
16.9R 30	W15	429	1475	667	4357	137	1.6	5290	3450	2550	2460	2300	2110
						A8	23	11650	7600	5620	5420	5070	4650

## 550 MULTIUSE

Size	Rim	Unloaded dimension		Loaded Static radius	Rolling circ.	PR Load Index	Infl. press	Recommended load, kg (lbs)									
		SW	OD					Speed, km/h (mph)									
		mm in	mm in	mm in	mm in	Speed Symbol		bar psi	Constant load						Cyclic application		
									Static	10 6	25 16	30 19	40 25	50 31	65 40	10 6	15 9
250/80R16IND	W8	270	814	373	2470	123D	4.4	3910	2130	1850	1790	1700	1620	1550	2890	2640	
		10.6	32	14.7	97.2	126A8	64	8610	4690	4070	3940	3740	3570	3410	6370	5810	
340/80R18IND (12.5/80R18)	11	343	1002	450	2982	138D	4.0	6270	3410	2970	2870	2725	2600	2360	4630	4220	
		13.5	39.4	17.7	117.4	143A8	58	13810	7510	6540	6320	6000	5730	5200	10200	9300	
365/70R18IND	W11	355	969	446	2872	135B	3.75	5010	-	2354	2311	2245	2180	-	3050	2510	
		14	38.1	17.6	113.1	142A2	54	11040	-	5190	5090	4940	4800	-	6720	5530	
405/70R18IND	W13	404	1021	468	3059	141B	3.75	5920	-	2781	2730	2652	2575	-	3610	2960	
		15.9	40.2	18.4	120.4	153A2	54	13040	-	6130	6010	5840	5670	-	7950	6520	
340/80R20IND	11	343	1052	480	3151	140D	4	6440	3500	3050	2950	2800	2670	2500	4760	4340	
		13.5	41.4	18.9	124.1	144A8	58	14190	7710	6720	6500	6170	5880	5510	10480	9560	
360/70R20IND	W11	355	1051	472.5	3121	124D	2.4	4260	2310	2020	1950	1850	1770	1600	3150	2870	
		14	41.4	18.6	122.9	129A8	35	9380	5090	4450	4300	4070	3900	3520	6940	6320	
360/80R20IND	DW11	358	1092	491	3265	143D	4	7070	3840	3350	3240	3075	2940	2725	5230	4770	
		14.1	43	19.3	128.5	147A8	58	15570	8460	7380	7140	6770	6480	6000	11520	10510	
300/80R24 IND	DW10	295	1092	502	3238	128D	3.2	4740	2580	2250	2170	2060	1970	1800	3500	3190	
		11.6	43.0	19.8	127.5	133A8	46	10440	5680	4960	4780	4540	4340	3960	7710	7030	
340/80R24IND (12.5R24)	DW11	343	1154	528	3439	135D	3.2	5750	3130	2730	2640	2500	2390	2180	4250	3880	
		13.5	45.4	20.8	135.4	140A8	46	12670	6890	6010	5810	5510	5260	4800	9360	8550	
360/80R24 IND (13.6R24)	DW12	357	1184	537	3554	138D	3.2	6270	3410	2970	2870	2725	2600	2360	4630	4220	
		14.1	46.6	21.1	139.9	143A8	46	13810	7510	6540	6320	6000	5730	5200	10200	9300	
400/80R24 IND (14.9R24)	DW13	404	1249	559	3703	144D	3.2	7480	4060	3540	3430	3250	3100	2800	5530	5040	
		15.9	49.2	22.0	145.8	149A8	46	16480	8940	7800	7560	7160	6830	6170	12180	11100	
420/65R24IND	W13	410	1158	527	3489	151A8	4	7940	4310	3760	3640	3450	3290	3000	5870	5350	
		16.1	45.6	20.7	137.4	146D	58	17490	9490	8280	8020	7600	7250	6610	12930	11780	
440/80R24 IND (16.9R24)	DW14L	441	1314	593	3965	149D	3.2	8630	4690	4090	3960	3750	3580	3250	6380	5810	
		17.4	51.7	23.3	156.1	154A8	46	19010	10330	9010	8720	8260	7890	7160	14050	12800	
460/65R24IND	DW14L	454	1209	547	3597	151D	3.2	9200	5000	4360	4220	4000	3820	3450	6800	6200	
		17.9	47.6	21.5	141.6	156A8	46	20260	11010	9600	9300	8810	8410	7600	14980	13660	
480/65R24IND	DW15L	480	1240	562	3730	146D	3.2	7940	4310	3760	3640	3450	3290	3000	5870	5350	
		18.9	48.8	22.1	146.9	151A8	46	17490	9490	8280	8020	7600	7250	6610	12930	11780	
540/65R24 IND	DW15L	545	1312	592	3953	154D	3.2	9780	5310	4630	4480	4250	4060	3750	7230	6590	
		21.5	51.7	23.3	155.6	158A8	46	21540	11700	10200	9870	9360	8940	8260	15930	14520	
400/80R28 IND (14.9R28)	DW13L	404	1352	613	4057	146D	3.2	7940	4310	3760	3640	3450	3290	3000	5870	5350	
		15.9	53.2	24.1	159.7	151A8	46	17490	9490	8280	8020	7600	7250	6610	12930	11780	
440/80R28IND (16.9R 28)	DW14L	440	1418	639	4240	151D	3.2	9200	5000	4360	4220	4000	3820	3450	6800	6200	
		17.3	55.8	25.2	166.9	156A8	46	20260	11010	9600	9300	8810	8410	7600	14980	13660	
480/65R28IND	DW15L	475	1339	607	4020	149D	3.2	8630	4690	4090	3960	3750	3580	3250	6380	5810	
		18.7	52.7	23.9	158.3	154A8	46	19010	10330	9010	8720	8260	7890	7160	14050	12800	
540/65R28 IND	DW18L	550	1412	649	4266	155D	3.2	10350	5630	4910	4750	4500	4300	3875	7650	6980	
		21.7	55.6	25.6	168.0	160A8	46	22800	12400	10810	10460	9910	9470	8540	16850	15370	
440/80R30IND (16.9R 30)	DW14L	434	1468	666	4436	153D	3.2	9490	5160	4500	4350	4125	3940	3650	7010	6390	
		17.1	57.8	26.2	174.6	157A8	46	20900	11370	9910	9580	9090	8680	8040	15440	14070	
480/80R30IND (18.4R 30)	DW15L	470	1531	695	4615	157D	3.2	10930	5940	5180	5010	4750	4540	4125	8080	7360	
		18.5	60.3	27.4	181.7	162A8	46	24070	13080	11410	11040	10460	10000	9090	17800	16210	
540/65R30 IND	DW18L	545	1461	666	4402	156D	3.2	10640	5780	5040	4880	4625	4420	4000	7860	7170	
		21.5	57.5	26.2	173.3	161A8	46	23440	12730	11100	10750	10190	9740	8810	17310	15790	





# TRACTOR DRIVE

## 550 MULTIUSE

Size	Rim	Unloaded dimension		Loaded	Rolling	PR	Infl.	Recommended load, kg (lbs)												
		SW	OD	Static radius	circ.	Load Index		Speed, km/h (mph)												
		mm in	mm in	mm in	mm in	Speed Symbol		bar psi	Constant load										Cyclic applications	
									Static	10 6	25 16	30 19	40 25	50 31	65 40	10 6	15 9			
600/70R30 IND	DW20	611	1602	727	4792	158A8	2.4	9780	5310	4630	4480	4250	4250	-	7230	6590				
		24	63.1	28.6	188.7	158B	35	21540	11700	10200	9870	9360	9360	-	15930	14520				
440/80R34 IND (16.9R34)	DW14L	441	1568	718	4737	155D	3.2	10060	5470	4770	4620	4375	4180	3875	7440	6780				
		17.4	61.7	28.3	186.5	159A8	46	22160	12050	10510	10180	9640	9210	8540	16390	14930				
480/80R34 IND (18.4R34)	DW15L	479	1629	739	4891	159D	3.2	11500	6250	5450	5280	5000	4780	4375	8500	7750				
		18.9	64.1	29.1	192.6	164A8	46	25330	13770	12000	11630	11010	10530	9640	18720	17070				
480/80R38 IND (18.4R38)	W15L	479	1728	786	5196	161D	3.2	12190	6630	5780	5590	5300	5060	4625	9010	8220				
		18.9	68.0	30.9	204.6	166A8	46	26850	14600	12730	12310	11670	11150	10190	19850	18110				
540/80R38 IND (20.8R38)	DW18L	546	1824	832	5497	167D	3.2	14490	7880	6870	6650	6300	6020	5450	10710	9770				
		21.5	71.8	32.8	216.4	172A8	46	31920	173600	15130	14650	13880	13260	12000	23590	21520				
600/65R38 IND	DW18L	593	1749	793	5270	166D	3.2	13800	7500	6540	6330	6000	5730	5300	10200	9300				
		23.3	68.9	31.2	207.5	170A8	46	30400	16520	14410	13940	13220	12620	11670	22470	20480				
650/65R38 IND	DW20B	645	1814	818	5450	171D	3.2	15870	8630	7520	7280	6900	6590	6000	11730	10700				
		25.4	71.4	32.2	214.6	176A8	46	34960	19010	16560	16040	15200	14520	13220	25840	23570				
650/85R38IND	DW23B	673	2067	913	6230	177D	2.4	18980	10310	8990	8700	8250	7880	7300	14030	12790				
		27	81.4	35.9	245.3	181A8	35	41810	22710	19800	19160	18170	17360	16080	30900	28170				
620/80R42IND	DW20B	644	2055	948	6170	177D	3.2	18980	10310	8990	8700	8250	7880	7300	14030	12790				
		25	80.9	37.3	242.9	181A8	46	41810	22710	19800	19160	18170	17360	16080	30900	28170				
650/65R42 IND	DW20A	638	1915	858	5795	171D	3.2	16330	8880	7740	7490	7100	6780	6150	12070	11010				
		25.1	75.4	33.8	228.1	176A8	46	35970	19560	17050	16500	15640	14930	13550	26590	24250				
710/70R42IND	DW23B	716	2053	939	6187	177D	2.8	18980	10310	8990	8700	8250	7880	7300	14030	12790				
		28.2	80.8	37.0	243.6	181A8	41	41810	22710	19800	19160	18170	17360	16080	30900	28170				





## About Alliance Tire Group [ATG]:

ATG develops, manufactures and markets superior quality Off-Highway tires globally under three well-known brands: Alliance, Galaxy and Primex. Specializing in Agriculture, Forestry, Industrial and OTR tires, the Group is one of the fastest growing players in the Off-Highway tire market.

ATG is dedicated to providing its customers with the lowest Total Cost of Ownership (TCO) through superior products and exceptional customer support services. ATG has a set of core values and strongly held beliefs focused upon the Group's commitment towards Innovative Technology, Customer Centricity, Excellence, Integrity, Accountability and Functional Cost Efficiency.

ATG owns two manufacturing plants; one in Hadera, Israel and the other in Tamil Nadu, Southern India. These facilities comply with strict international standards of manufacturing and are ISO certified. The products manufactured meet environmental compliances which are in line with the global markets. ATG has four R&D centres, one each in India, Israel, South Africa and the United States of America, which makes it possible to engineer products to specific market need. ATG's regional offices are present in India, Israel, South Africa, Netherlands and the United States. Also enhancing ATG's global reach are its representatives and offices in countries such as Argentina, Australia, Brazil, Canada, China, France, Germany, Iberia, Italy, Scandinavia, Turkey, Ukraine and United Kingdom.

For our online catalog and for more details about Alliance Tire Group, please visit: [www.atgtire.com](http://www.atgtire.com)

### OFFICES:

#### ATC Tires India Pvt. Ltd.

Unit No. 6 & 7, High Street Phoenix A Wing, Phoenix Mills Compound, 462 Senapati Bapat Marg, Lower Parel, Mumbai - 400 013. Tel: +91 22 39579600, Fax: +91 22 39579699.

#### Alliance Tire Company Ltd.

PO BOX No. 48  
Hadera 38100 Israel.  
TEL: 972 4 624 0520  
FAX: 972 4 624 0555

#### Alliance Tire Europe BV

Vang 14A, 3320  
PO BOX: 149, 4660AC  
Halsteren, The Netherlands  
Tel: +31 (0) 164 676270  
Fax: +31 (0) 164 676289

#### Alliance Tire Americas Inc.

201 Edgewater Drive, Suite 285  
Wakefield, MA 01880  
Tel: 781-321-3910  
Toll Free: 800-343-3276  
Fax: 781-322-2147

#### Alliance Tire Africa (Pty) Ltd.

PO BOX 19094, Linton Grange  
Port Elizabeth, 6015, ZA  
Tel: 27 41 3651097  
Fax: 27 41 3653304

Media contact: [contact@atgtire.com](mailto:contact@atgtire.com)

#### Regional offices & representatives

• Argentina • Australia • Brazil • Canada • China • France • Germany • Iberia • India • Israel • Italy • Russia • Scandinavia • South Africa • The Netherlands • Turkey • Ukraine • UK • USA

Distributor:

#### Disclaimer:

Tire specifications mentioned in this document are subject to change with no prior intimation or notice. Please visit [www.atgtire.com](http://www.atgtire.com) for updated information and details.



## About Alliance Tire Group [ATG]:

ATG develops, manufactures and markets superior quality Off-Highway tires globally under three well-known brands: Alliance, Galaxy and Primex. Specializing in Agriculture, Forestry, Industrial and OTR tires, the Group is one of the fastest growing players in the Off-Highway tire market.

ATG is dedicated to providing its customers with the lowest Total Cost of Ownership (TCO) through superior products and exceptional customer support services. ATG has a set of core values and strongly held beliefs focused upon the Group's commitment towards Innovative Technology, Customer Centricity, Excellence, Integrity, Accountability and Functional Cost Efficiency.

ATG owns two manufacturing plants; one in Hadera, Israel and the other in Tamil Nadu, Southern India. These facilities comply with strict international standards of manufacturing and are ISO certified. The products manufactured meet environmental compliances which are in line with the global markets. ATG has four R&D centres, one each in India, Israel, South Africa and the United States of America, which makes it possible to engineer products to specific market need. ATG's regional offices are present in India, Israel, South Africa, Netherlands and the United States. Also enhancing ATG's global reach are its representatives and offices in countries such as Argentina, Australia, Brazil, Canada, China, France, Germany, Iberia, Italy, Scandinavia, Turkey, Ukraine and United Kingdom.

For our online catalog and for more details about Alliance Tire Group, please visit: [www.atgtire.com](http://www.atgtire.com)

### OFFICES:

#### ATC Tires India Pvt. Ltd.

Unit No. 6 & 7, High Street Phoenix A Wing, Phoenix Mills Compound, 462 Senapati Bapat Marg, Lower Parel, Mumbai - 400 013. Tel: +91 22 39579600, Fax: +91 22 39579699.

#### Alliance Tire Company Ltd.

PO BOX No. 48  
Hadera 38100 Israel.  
TEL: 972 4 624 0520  
FAX: 972 4 624 0555

#### Alliance Tire Europe BV

Vang 14A, 3320  
PO BOX: 149, 4660AC  
Halsteren, The Netherlands  
Tel: +31 (0) 164 676270  
Fax: +31 (0) 164 676289

#### Alliance Tire Americas Inc.

201 Edgewater Drive, Suite 285  
Wakefield, MA 01880  
Tel: 781-321-3910  
Toll Free: 800-343-3276  
Fax: 781-322-2147

#### Alliance Tire Africa (Pty) Ltd.

PO BOX 19094, Linton Grange  
Port Elizabeth, 6015, ZA  
Tel: 27 41 3651097  
Fax: 27 41 3653304

Media contact: [contact@atgtire.com](mailto:contact@atgtire.com)

#### Regional offices & representatives

• Argentina • Australia • Brazil • Canada • China • France • Germany • Iberia • India • Israel • Italy • Russia • Scandinavia • South Africa • The Netherlands • Turkey • Ukraine • UK • USA

Distributor:

#### Disclaimer:

Tire specifications mentioned in this document are subject to change with no prior intimation or notice. Please visit [www.atgtire.com](http://www.atgtire.com) for updated information and details.